

Index

References in this index are to page numbers in the text.

The page numbers in *italics* are references to figures, those in **bold** are to definitive information.

The Preface, Acknowledgments, Abbreviations & Acronyms (pp. vii-xv) and Glossary (pp. 485-509) have not been indexed.

The index is arranged alphabetically. Prepositions and the like at the beginning of subheadings have been ignored in determining subheading order. The ampersand '&' has been used in place of the word 'and'.

A

- Abrasion test (Los Angeles)** 13
- Absorptive surfaces**, effect on algorithm 342, 344, 373
- Accidents** 31, 419; *see also* Crashes
- Acts**, *see* HSE, HSNO, LGA, RMA
- Additives** 272-278; selection for design 360-361; *see also* Adhesion agent, AGO, Antifoaming agent, Cutter, Diesel, Flux, Heavy fuel oil, Polymer, Precoating, Rubber
- Adhesion agent** 12, 52, 273-275, 274, 275, 301-302, 356, 361, 428, 472, 475; in precoating 11, 349; how they work 273-274, 275; & chip cleanness 275, 364, 472; in PMBs 301, 302; in chipseal design 361, 371, 429, 430; timeline 5; in primers 52; in first coat seals 356
- Advantages of chipseals** 4, of primes 168; of emulsions 285, 290, 302, 360, 469
- AGD**, *see* Average Greatest Dimension
- Ageing of bitumen** 270; in chipseal 93, 100-102, 101; & cracking 101; effect of 102; end of seal life 101, 102; hardening 270-271; RTFO test 265
- Aggregate** 4, 13, 46; for chipseal 48-49; & construction 18, 407, 454, 479; & environment 213; for granular basecourses 225, 227-228; & priming 165; production (crushing, screening) 48, 257-258, 308-310; quality control 311; rock extraction 308; size grade 307, 316-319; size, shape changes 13, 343, 356; & PSV 125, 125, 131, 184; for slurry seals 66-71, 320; sources 305-306; stockpiling 311; tests 312-319; types 307; *see also* Chip, Calcined bauxite, Synthetic aggregates
- Aggregate tests** 312-319; production property tests 315-319; source property tests 312-315; *see also* Chip properties & tests
- AGO** 27, 272, 278, 283, 302, 355, 359; in chipseal design 359, 360, 428; loss over time 95-96; worked example 371, 428, 429, 431; *see also* Additives, Diesel, Flux
- ALD**, *see* Average Least Dimension, ALD:AGD (shape), ALD/16 rule
- ALD:AGD (shape)** 6, 319, 343, 374
- ALD/16 rule** 353, 372, 373-374
- Algorithm**, *see* Design algorithm, Treatment selection algorithm
- Alligator cracking** 79, 80; RAMM definition 80; *see also* Cracking
- Anionic emulsion**, *see* Bitumen emulsion
- Antifoaming agent** 278; *see also* Additives
- Application rate** 15-18, 93, 102, 116, 168, 238; control of 390-391, 396-398, 402, 405-406, 435; *see also* Binder, Bitumen emulsion, Chip and PMB application rates, Calibration
- Aquaplaning** 241; *see also* Skid resistance, Water film
- Area-wide Pavement Treatment (AWPT)** 142, 154, 155, 163, 241, 244, 245, 251, 470, 476-479
- Asphalt**, *see* Asphaltic concrete
- Asphaltic concrete (asphalt, HMA)** 112, 113, 261, 265, 276-277, 299, 354, 471-472; absorptive surfaces 252-253, 342; bridge decks 191-192; defects in 82, 244, 249, 237; design & testing 177, 265; equipment 407, 408; frost 196, 198, 201-202; noise 210-211, 211; OGEM 72, 252, 253, 342, 463; OGPA 72, 176, 187, 202, 248, 252, 253, 253, 299, 342, 477; preseal prep 225, 226, 236, 237, 238, 244, 249, 249, 252, 253, 253; repairs 477; in rigid pavements 44, 165; roadmarking 187-188; SAMI 299; seal selection 141, 146, 151, 163, 164-165, 172, 176, 187, 216, 248, 356, 477; soft substrate 112, 113, 341, 354, 463; in surfacings 44, 49, 66-68, 72-73, 72, 82, 141, 165, 168, 291, 294, 295, 296; *see also* Membrane seal, Open-graded mixes, SAMI
- Asset management**, of roads 137-143, 138; of pavements 142-150; condition data 140, 144-145; costs of 150-151, 151, 153; current work programme 143; design life & calculation 152, 153; development 19-20; dTIMS 19, 145; end of life cycle 155; exception report 144, 145; forward works programme 138, 142-143, 146-147; identification systems 145-146; implementation 138, 143; inputs 138, 139-140; inventory of assets, condition 144-145; life cycle management 139, 150-155; maintenance 145; NOMAD 147; optimisation 141, 142; options 141;

- outputs 138, 142-143; predicting performance 140; prioritisation 138, 141-142; process 138, 138-143; RAMM, function of 144-145; risk assessment 138, 141-142, 145-146, 147, 149; theory of 6; timing of reseals 156; treatment identification 145-146, 146; treatment lengths for management 139; treatment selection 144; unscheduled reseals 156; worked example (pavement life) 152, 153; *see also* Life cycle of chipseal, RAMM
- Asset manager & Seal designer roles** 137, 142
- Average Greatest Dimension (AGD)** 96, 301, 319, 319, 426, 440, 453; *see also* Average Least Dimension, ALD:AGD (shape)
- Average Least Dimension (ALD)** 5, 6, 103-105, 104, 316-318, 317, 318, 331-333, 335, 338, 339, 344, 345, 348, 432; adjustment for ALD 342, 346-347, 347; binder application rate 347-349; chip application rate 365-369, 368, 432, 440; & chip selection 13, 367; chip shape (ALD:AGD) 6, 319, 343, 374; chip size 13, 316-319; definition 316; design aspects 331-333, 335; measurement 316-318; & multicoat seals 105, 152, 347-348, 367-369, 368; for repairs 246, 246; & single coat seals 103-104, 104, 152, 366-367; & traffic 103, 152, 333, 346-347; worked example 370-374; *see also* ALD:AGD (shape), ALD/16 Rule
- AWPT**, *see* Area-wide Pavement Treatment
- B**
- Bandaging** 174, 238-240, 239, 297; *see also* Crack sealing
- Base**, *see* Basecourse
- Basecourse** 42, 43, 44, 46, 47, 195, 221-222, 223, 224, 225, 226, 227-228, 228, 236-238; aggregate for 12; defects in 229; definition 44; & design 335, 356; failure 82, 111, 229-231; preparation 193, 451, 479; & stabilisation 231-232, 286; surface finish 227-228
- Basecourse density** 227
- BCA 9904 compliance** 25, 26, 27, 28, 30-32, 34, 214, 262, 277, 387, 399, 400, 401, 427, 440, 450, 456
- BCA E/2 compliance** 380, 382, 384, 390, 394, 395, 397, 399, 401, 441, 443, 449, 453
- Benefit/cost ratio** 120, 154
- Benkelman Beam** 243
- Berm**, *see* Shoulder
- Binder** 46, 47, 48, 261-271; additives, use in 272-278; bulk supply, transport 10; texture loss 462-466; for cold conditions 203; definition for bitumen emulsion 280; hardening 94-102, 111, 119; history 3, 4-5, 7-12, 8, 9; materials 425; nomenclature 261-262; research 10, 103; sources 7-9; *see also* Bleeding, Flushing, Hazards, Life Cycle, Texture
- Binder application rate** 301, 443, 445; calculations for bitumen binder 428-431, for bitumen emulsion spray rate 447-448, for PMB spray rate 452-453; for cape seal 348; for cracking 174, 238-240; effect of HCVs 338-339, of temperature 337, of texture 332-333, 339, of variables 345-347; for first coat seal 355; for geotextile seal 349; Hanson's equation 332; multiple coat seals 347-348; PMB seals 174, 298-299, 304; primes 168; precoating 349-350; for racked-in seals 368; for remedies 238, 240, 245-246, 472, 474; residual binder 347-350; for sandwich seal 348-349; for second coat seal 356-359; traffic factor 333; for two coat seal 347-348; variables 341-344; for wet lock seal 476; worked example 370-374
- Binder (residual) in chipseal design** 347-354, 355-359; first coat seal 355-356; geotextile seal 349; second coat seal 356-359; worked example 370-374
- Binder hazards** 26-32; blending 28, 400-401; pollution 214; PPE, clothing for 28, 29; presence of water 28; transferring 28, 401
- Binder heating for construction** 440; heating factors for bitumen 434, for emulsion 448; temperatures for bitumen 432-434, for emulsion 448-449
- Binder materials**, *see* Binder
- Binder pressure gauge** 395; BCA E/2 compliance 395
- Binder residual**, *see* Binder (residual) in chipseal design
- Binder rise** 85, 98, 117, 117, 118, 229, 301, 341, 353, 453, 461, 462, 463-464, 463, 465; *see also* Vapour venting
- Binder run-off** 62, 74, 441, 447-448, 450
- Binder spraying**, calculation for spray rate for bitumen binder 432, for emulsion 447-448, for PMBs 452-453; control of application rate 396-397; output rate 396-397; heating factors for bitumen binder 434, for emulsion 448; spray temperatures for bitumen binder 432, 433, 434, for emulsion 448-449, for PMBs 453; worked examples 429-431
- Binder:stone ratio** 59, 173, 177-179, 180, 470, 471
- Bitumen**, *see* Binder
- Bitumen Burns Card** 19, 30, 31-32; *see also* Burns, bitumen
- Bitumen for emulsion**, *see* Bitumen emulsion
- Bitumen for PMBs**, *see* PMBs
- Bitumen distributor** 379, 380; calibration of 389-390; circulation systems 390-393, 392, 393; early types 1-2, 9, 14-15, 14, 15, 17, 17; hazards 440; heating binder 440; instrumentation 394-396; output 396-397, 397; pressure gauge 395; pumping systems 390-393, 391; pumps 397, 397; speed control of 395; spray control 384-386, 398; strainer (screen) maintenance 396; temperature measurement 395-396

- Bitumen emulsion** 11, 279-290, 446-451; advantages of 290, 360; anionic 280-283, 280; breaking 282-283, 450-451; cationic 280-283, 281, 282; continuous phase 279-280; curing 283, 360, 450-451; design 360-363; dispersed phase 11, 279-280; emulsifiers 279-280; formulation 283-284; grades 285-286, 446-447; handling 286-287, 449-450; heating factors 448; manufacture 280-281; material selection 446-447; plant 449-450; sampling 287-288; settlement 287, 446; spray rate calculations 447-448; storage 286-287; testing 288-289; upcreaming 287, 446; *see also* PME, Slurry seal
- Bitumen emulsion application** 302, 447-448; application temperature 447-449
- Bitumen emulsion construction** 446-451; heating factors for emulsion 448; spray rate calculations 447-448; spray temperatures 448-449
- Bitumen plant**, *see* Equipment for chipsealing
- Bitumen properties** 261-271; ageing 270-271; ductility 266; durability 266; flash point 26, 264; hardening 270-271; ignition point 26; modulus 266-270; nomenclature 261-262; penetration grade, testing 262; RTFO test 265; softening point 271; solubility 264; stiffness 267; viscosity 10-12, 263-264
- Bleeding** 85, 86, 87, 93, 238, 241, 243, 251, 298-299, 300, 301, 303; effect of diluent 94, 356, 357, 359, 361; definition 86; repair 463, 464, 464, 465, 465-466, 468, 469
- Blending hazards** 28, 400-401
- Block cracking** 79, 82; RAMM definition 82; *see also* Cracking
- Breaking of emulsion** 282-283, 450-451
- Bridges**, seal selection 188-194; abutments 189, 190, 193, 193; decks 188-192, 194
- British Pendulum Tester (BPT)** 120, 182, 315; PSV test 200, 313, 314, 315
- Brooms (Brooming)** 228, 229, 330, 254, 355, 409-412, 411; *see also* Drag, Rotary, Suction, and Vacuum brooms; Sweeping
- Burning (pavement)** 249-250
- Burns**, bitumen 19, 30, 31-32; *see also* Hazards
- C**
- Calcined bauxite** 48, 73, 182, 191, 306
- Calibration for binder application** 396-397; bitumen distributor 389, 390; chip spreading plant 405; early methods 18; spraybar 384; start-finish 388, 389
- Cape seal** 69-71, 69, 71, 164, 172, 176, 217; design 71, 348, 367
- Carriageway** 41; terminology 42-43
- Cationic emulsion**, *see* Bitumen emulsion
- Cement for slurry seal** 66-67, 321-322; for stabilisation 231-232; for recycling 179
- Chip** 46, 48-49, 305-319; aggregate types 307; broken faces 319; crushing 308-310; extraction 305, 308; processing 307-310; PSV 129-130, 131; PSV equation 130; screening 308-310; shape 6, 130-131, 319, 343, 374; skid resistance 129-130
- Chip application rate** 17-18, 365-369, 432, 435-438, 436, 437; 2004 design algorithm 365-366; cape seal 367; geotextile seal 369; Hanson's research 5-6, 6, 13, 332; racked-in seal 368; sandwich seal 369; single coat seal 336-367; two coat seal 369; & voids 366; voidfilling seal 367; worked example for single coat 370-374; worked example for chip volume 435
- Chip loss** 82-83, 111, 466-468, 467, 468; causes 362-365, 363, 466; prevention 480-481; repairs 245-246; types 467; *see also* Ravelling, Scabbing
- Chip production** 48-49, 305-311, 309, 310; crushing 308-310, 309, 310; quality control 311; screening 308-310, 308, 309, 310; size grade 46, 48, 49, 108, 130-131, 307, 316, 317-318, 317; sources of aggregate 305-306, 307, 308; *see also* Chipseal selection
- Chip properties & tests** 311-321; AGD 319; ALD 316-319; angularity 319; BPT test 315; broken faces 13, 319; cleanness 6, 13, 312, 313, 315-316, 316, 364, 472; crushing resistance 312; grade 13, 316, 317, 318; & skid resistance 119-129, 129-130; particle size distribution 67, 307, 318, 320; PSV 13, 48, 129-130, 131, 182, 313, 314-315, 314; PSV equation 130; shape 6, 130-131, 319, 343, 374; size (ALD) 130-131, 316-319; size uniformity 318-319; for slurries 320-321; weathering resistance 312-313
- Chip selection** 312-315, 314, 367
- Chip spreader** 1-2, 402-406, 403, 405; calibration 405; fan-tail 1, 18; Flaherty 18; roller 18, 402-404, 403; self-propelled 404-405, 405; short wheel-based tip truck 1-2; trucks 1-2, 402; truck-mounted roller 402-404, 403
- Chip spreading hazards** 33-34; 404, 425, 432, 435-438, 436-437; worked example for chip volume 435
- Chipseal advantages of** 3-5, 49; definition 46-49, 47; Hanson's work 5-7, 331-332; history 3-21, 4, 5; philosophy 4-7; technology 41-76, 77-87; terminology 41-46; types 49-66, 165-169; *see also* Aggregate, Binder, Chip, Chipseal surfacings, Design algorithm, Life cycle of chipseal
- Chipseal construction**, *see* Construction of chipseal
- Chipseal defects**, *see* Defects
- Chipseal design**, *see* Design algorithm

- Chipseal failures**, *see* Failure of chipseals
- Chipseal hazards**, *see* Hazards
- Chipseal materials**, *see* Materials for chipsealing
- Chipseal plant**, *see* Equipment for chipsealing
- Chipseal repairs**, *see* Pavement repairs, Preseal preparation
- Chipseal selection**, exception reporting for 180-181; flow charts for 163, 171, 172, 180; forward works programme 142-143; intelligent treatment identification 145-146, 170; investigations for 170, 171-181, 172, 194, 199, 233, 341-343, 420-422; life cycle 139, 150-155; location 421, 422; options 163, 167-169, 172, 176, 178-180, 180, 188, 194, 212, 216, 217; sealing sequences for 163, 172; surfacings for 49-66; systems for 144, 172
- Chipseal selection for bridge abutments** 189, 190, 191, 193, 193; bridge decks 188-194, 192; coarse textured surfaces 173; community issues 204, 205, 208-209, 212-217, 421-422; cracked surfaces 174; engineering issues 171-181; environmental reasons 212-214; first coat treatments 165-168; flushed surfaces 171; frost, ice & snow 194-203; layer instability 177-179; noise reduction 204-212; pretreatments 50, 53, 168, 225, 252, 253, 254, 351; prime coats 168; principles 163-165; road user safety 181-187; roadmarking contrast 187-188; second coat treatment 169; site assessment 170-172, 172, 194, 199, 341-343, 420-422; smooth surfaces 171, 172; stressed surfaces 98, 152, 153, 167, 171, 174-177, 182, 184, 185-186, 245, 354, 426, 440, 445, 466, 472, 477; texturing seal 166, 168, 225, 244, 252; traffic noise 204-208; treatments 165-168; treatment lengths 139, 140-142, 178, 181; voidfill 173; water spray 186-187; *see also* Bridges, Chipseal surfacings, Community & chipseal selection, Frost, ice & snow, Life cycle of chipseal, Skid resistance, Traffic noise
- Chipseal surfacings** 49-66, 166-169; *see also* Dry lock, Enrichment, First coat, Multicoat, Pretreatment, Prime coat, Racked-in, Reseal, SAM, Sandwich, Second coat, Single coat, Two coat, Two coat as first coat, Voidfill, Wet lock seals
- Chipseal variables**, *see* Design variables
- Chipsealing**, *see* Chipseal, Chipseal selection, Chipseal surfacings
- Chipsealing hazards**, *see* Hazards
- Chipsealing materials**, *see* Materials for chipsealing
- Chipsealing operations**, *see* Construction of chipseals
- Chipsealing plant**, *see* Equipment for chipsealing
- Chipsealing site assessment**, *see* Chipseal selection
- Circulating systems** 390-393, 392, 393; *see also* Bitumen distributor, Pumps & pumping systems
- Cleanness of chip** 275, 315-316, 316, 364, 472
- Clothing for chipsealing**, *see* PPE
- CMA use & hazards** 201
- Coal tar** 3-7, 12; carcinogenic properties 7; as primer 12
- Cold conditions**, *see* Frost, ice & snow
- Combination roller** 409, 409
- Community & construction**, check list 425-426, 456; liaison 33, 34, 215, 421-422
- Community & chipseal selection** 143, 212-217; aesthetics & appearance 216; complaints 214-215; cost 150; fuel consumption & tyre wear 217; noise 204, 205, 208, 210, 215; pedestrians & cyclists 216; tracking 215-216
- Compaction** 5, 176, 193, 227; effect on performance 96-97; effect on voids 98, 103, 408, 440; trials 96-97, 96, 97; *see also* Rolling
- Condition**, *see* Asset management
- Construction of bitumen emulsion seal** 446-451; *see also* Bitumen emulsion
- Construction of chipseal 419-456**; check list 425-426; consumables 423; contract requirements 420; design assessment 422; drum rolling 440 equipment 423; materials 424; on the day 438-446; organising 419, 425-426; plant 380-412, 423; programming 419-426; rolling 425, 426, 438-440, 439, 451, 454; standards 138; traffic management 423
- Construction of PMBs** 451-454; *see also* PMBs, PMB construction
- Construction plant**, *see* Equipment for chipsealing
- Contamination of chip**, precoat, seal 277, 311, 424, 466; run-off 213-214, 254, 276, 302, 419, 456
- Contract requirements** 10, 236, 254, 303-304, 419, 420
- COPTTM compliance** 25, 28, 33, 387, 401, 423, 438
- Corners**, effects of 174-175, 404
- Costs** 120, 142-143, 150-151, 152, 154-155, 176, 244, 455; worked example 153, 155; *see also* Asset management
- Crack sealing** 238-240, 297-298
- Cracking** 52, 79-82, 100-102, 106-107, 111, 113, 118-119, 172, 174, 190, 226, 236-240, 359, 370; & ageing, failure 101, 111; precautions 240; repairs for 236-240, 239; in structural layers 237-238; in surface layers 238-240; using PMBs 295, 297-300, 304, 451
- Cracking types 79-82**; RAMM definitions 77-82; *see also* Alligator, Block, Longitudinal, Shrinkage, and Transverse cracking
- Crashes** 119, 120-122; Investigatory Levels 121; policies for 119-120; & seal selection 181-186; & skid resistance 119-121, 181
- Crumb rubber** 11, 297

Crushing 308-310; *see also* Chip production

Crushing resistance test; *see also* Chip properties & tests

Curing of binder 97; of bitumen 264, 421, 450-451; of bituminous emulsion 283, 360; green-strength 290; of primes 168; of slurry 321

Current work programme 138, 143, 170

Cutback, *see* Cutter

Cutter (Cutback) 46, 51, 93-94, 261, 272, 360, 427-428; hazards 27, 28; how it works 93, 94, 252; for first coat seal 355-356; in primer 12, 51, 52, 168; worked example 429-431; *see also* Kerosene

Cutting back for binder design 94-96, 361-365; cutback 360; effect of emulsion 363; effect of rolling & traffic 363; effect of shade 362-363, 364; factors affecting design 364; flux 360; objectives 361-362; process 362; viscosity on road 363-364

Cutting back for construction 427-428; for first coat seal 355-356; second coat reseal 358; spray temperature 433; volume required 428; worked examples 429-431

D

Dangers, *see* Hazards

Dangerous Goods Act & Regulations 26

Databases, *see* Asset management, RAMM

Decks for bridges, *see* Bridges, seal selection

Defects 77-87, 77, 79; rubber build-up 480; *see also* Bleeding, Chip loss, Cracking, Deformation, Edge break, Flushing, Potholes, Pumping, Ravelling, Roughness, Rutting, Scabbing, Shear failures, Shoving, Skid resistance, Texture loss, Tracking

Deformation 77-78, 77, 241-242; *see also* Defects

Delamination of bridge deck 189; of PMB 468; of slurry seal 68

Deleterious matter, removal of 253-254; lichen, weed spraying 254; *see also* Brooms

Depressions, causes & repairs 241-242

Design algorithm 340-347; 2004 algorithm 344; adjustment of 341-344; binder selection 360-365; Bituminous Sealing Manual 1993 (BSM) 334, 339, 344; chip application rates 365-367; chip selection 367-369; chipseal selection 150-156; TNZ & Austroads algorithms 340, 340, 341; costs 150-151, 151, 153, 155; derivation of 2004 algorithm 337-339, 344; development of 4-7, 331-344; end of life 154, 154, 155; equations for seal life 152; Hanson's input 5, 13, 331-332; HCVs 338-339; history 4-5, 331-335; impact of life cycle 150-156, 154; & pavement life 151-155, 154; practical aspects 350-354; principles of chipsealing 4-7; RD286 332, 334, 340, 340; research (theory) 6-7, 331-341;

residual binder 355-365; sand circle T/3 equation 333; selection of additives 360-365; selection of binder type 360; sensitivity of 2004 algorithm 344-347; texture 332-333, 333, 339, 344; traffic factor 333; for voidfill 59; worked example 153, 370-374; *see also* Chipseal selection, Design variables

Design life 108, 109, 150-155; worked example 153, 155

Design variables 341-344, 350-354; absorptive surface 342; chip shape 343; high stress sites 354; homogeneous sections 350-351; low traffic volume 343-344; pavement hardness 354; sensitivity to changes 344-345, 346-347; soft substrate 341-342; spray runs 350; steep grades 342-343; texture variation 352-354; traffic segmentation 351; traffic volume 351-352; urban reseals 343-344

Detritus, *see* Deleterious matter

Diesel 26, 27, 96, 272, 276, 302, 349; *see also* AGO, Flux

Digout 236-237, 243, 469

Digout & replace 236, 242, 470

Diluent for construction, *see* AGO, Cutter, Flux, Heavy fuel oil

Diluent loss 94-96, 95; of AGO 95, 96; of kerosene 94-95, 95; trials 94-95, 96; turpentine 95

Diluent & chip 472-473, 473

Dipstick 394

Distributor, *see* Bitumen distributor

Drag brooming 18, 229, 230, 404, 406, 409, 411, 412

Drainage repairs 234

Drum roller 18, 440

Dry lock seal 63-64, 63; design 164, 176, 343, 348, 354

dTIMS 19, 145

Ductility of bitumen 266

Durability of bitumen 266

Duval attrition test 13

E

Edge break 84, 235-236

Edge rutting 235

Elastomers, *see* Polymers

elv (equivalent light vehicles) 103-105, 104, 105, 152, 153, 334, 335, 336, 338

Embedment of chip 6, 102, 103, 112-113, 173, 203, 205, 242, 285, 333-335, 334, 338, 339, 341, 407-409, 462-463, 472, 474

Employers' duty to staff 25

Emulsion, *see* Bitumen emulsion, Construction of bitumen emulsion seal, PME emulsion, Slurry seal

- Emulsifiers** 279-281
- End-of-life**, *see* Life cycle of chipseal, Performance of chipseal
- Engineering issues**, *see* Chipseal selection
- Enrichment seals** 73-74, 163, 164, 169, 476
- Environment & construction** 25, 34, 51, 212-214, 217, 420-421, 444-456; checklist 456; & emulsion 279, 290; energy efficiency 213, 455; & precoated chip 278, 424; waste minimisation (recycling) 213, 455; water management 213-214, 456; *see also* Chipseal selection
- Environmental conditions for chipsealing**, *see* Frost, ice & snow, Weather
- Equilibrium Skid Resistance (ESR)** 125, 125, 127-129; *see also* Skid resistance
- Equilibrium SCRIM Coefficient (ESC)** 127-129, 129; correction for 128-129; & MSSC 126-129, 127, 128, 129; for maintenance funding 128; PSV 125-126, 125
- Equipment for chipsealing** 380-412; *see also* Binder pressure gauge, Bitumen distributor, Brooms, Chip spreader, Circulating systems, Combination roller, Dipstick, Drum roller, Hazards, Heating systems, Instrumentation, Pneumatic-tyred roller (PTR), PPE, Pumps & Pumping systems, Rollers, Spraybar, Strainer (screen), Tachometer
- Evaporation of cutter** 94-95, 95; of flux 96
- Events**, effect on construction 421-422
- Exception reporting** 145, 180-181, 182
- Expected or average seal life**, *see* Life cycle of chipseal
- Explosions** 27
- F**
- Fabric**, use of 476-477; *see also* Geotextile seal
- Failure of chipseals** 461-481; *see also* Ageing of bitumen, Binder rise, Bleeding, Chip loss, Cracking, Embedment, Flushing, Life cycle of chipseal, Performance of chipseal (temperature, traffic), Re-orientation of chip, Skid resistance, Texture loss
- Failure localised** 470-476; major 476-479
- Failure of granular basecourse** 229-231; pavement 236-253; by shear failure 242-244; of stabilised pavement 231-232; of surface texture 245-253
- Falling Weight Deflectometer (FWD)** 243
- Fan-tail spreader** 1-2, 18; *see also* Chip spreader
- Fatigue cracking** 100-102, 101, 299
- Fire hazard** 27
- Fire triangle** 27
- Firefighting** 419, 420
- First aid**, Bitumen Burns Card 31-32, courses & manuals 25; treatment for burns 30-32
- First coat seal** 1-2, 12, 47, 50, 50-51, 163, 164-167, 166, 463, 468, 471; design 355-356, 365-367, 370, 428, 447; failure 112; preparation 223, 225-229; prime coat 51-52, 168; on stabilised pavement 231-232; *see also* Single coat, Single coat seal
- Flaherty chip spreader** 18
- Flame tube heating**, *see* Heating systems
- Flash point of bitumen** 26, 264; of kerosene 26
- Flexible pavement** 44
- Flow charts** 135, 148, 149, 163, 171, 172, 179, 180
- Flushing** 59, 84-86, 85, 94, 100-103, 101, 111-117, 114, 117, 118, 135, 142, 156, 169, 171-173, 172, 178-179, 181, 226, 337, 341, 343; remedial treatment 247-251, 247, 249, 250, 251, 348-350, 427, 444, 459-460, 462-464, 465, 471-476, 473, 476-479; *see also* High pressure water treatments
- Flux** 95-96, 226, 272; & design 359, 360, 371; for construction 401, 428, 432; *see also* AGO, Diesel
- Foaming** 27, 278, 291, 449
- Fog coat** 73-74, 164
- Footpath defects** 77; surfacing for 67, 216
- Forward works programme** 138, 142-143, 146-147, 149, 170; impacts on schedules 148-150; & management 147; & NOMAD 147
- Freeze-thaw effects** 111, 229; *see also* Frost, ice & snow
- Fretting**, *see* Chip loss, Ravelling
- Friction**, *see* Skid resistance
- Frost**, ice & snow 194-203; binder selection 203; chip selection 202; chipseals for 200, 202, 203; CMA use 201, 201; dew 197-198; effect of shade 198; effect of texture 200, 200; formation of 195-199; freeze-thaw, frost heave effects 111, 229; hoar frost 196-197; identifying sites 198-199; management for 200-201; resurfacing for 201-203; RWIS 199; & skid resistance 198-200, 199; snow plough damage 55, 57, 197, 202; thin ice 197; timing 203; *see also* Temperature (weather), Weather
- G**
- Gangbar, Gangsprayer**, *see* Spraybar
- Geotextile seal** 74-76, 74, 75, 164; design 349, 369; fabric use 476-477; repairs 174, 191, 192, 240, 470, 476-477
- Grade chip size**, *see* Chip production, Chip properties & tests, Chipseal selection
- Gradient steep**, effects of 175, 185
- Granular basecourses** 225, 232, 235-239; criteria for 227; effect of fines layer 228; failure 229-231; preparation 225, 227-228
- Granular overlay & repair** 179, 238, 470, 477, 479
- Gravel**, *see* Aggregate
- Greenfield sites** 168

Green-strength 290, 446
GripTester 120, 182
Gritting 229, 471
Ground water contamination 278, 456
Guardrail 187, 445

H

Hairline cracking, *see* Cracking
Hand spraying 7, 9, 14, 15, 14, 17, 47, 192, 380, 381, 388, 389, 392, 393, 415-416, 444-445, 444; hazards 7, 8, 14-15, 14, 17; *see also* Spraying
Hanson 4, 5-6, 6, 13, 21, 331-355, 366; Hanson's equation 332
Hard substrate, *see* Soft substrate
Hardening of bitumen 98-99, 117, 265, 270-271; & RTFO test 265; *see also* Ageing of bitumen
Hardness & modulus 266-270
Hazards, BCA 9904 compliance 387, 400; legal requirements 26; safety requirements 25-34
Hazards from binder 25-32, 400-401, 440, 427; blending 400-401, 427; burns 19, 30-32; chipsealing materials 7-8, 19-20, 26-27; chipsealing operations 16-20, 28-34, 400-401, 420, 424, 427, 440; coal tar 7; explosions 27; fire 27; heating binder 440, 427; PMBs 294, 454; precoated chip 424; primer 12, 51; spraybars 386-387; traffic 33; transferring binder 28, 401; vapour in confined spaces 27-28; water in bitumen 27-28, 449
Hazards to community 34, 215; environment 25, 34, 214; health 26-32
HCV, *see* Heavy vehicles
Heating binder for construction 433, 434; *see also* Heating systems
Heating factors for bitumen 434; for emulsion seal 448
Heating systems 8, 16-17, 399-400; electrical heating 17, 400; flame tube 16, 400; hazards 399; oil 17
Heavy commercial vehicles, *see* Heavy vehicles
Heavy fuel oil 272, 359; *see also* Cutter, Flux
Heavy vehicles (HCV), effect on binder application rate 338-339; effect on chipseal 6-7, 78, 130, 130, 152, 175, 187, 205; elv 103, 104, 105, 152, 153, 334, 335, 336, 338; noise of 204, 210-212; seal selection for 167; & water spray 186; worked example 153
High pressure water treatments 168, 178, 213, 225-226, 248-251, 249, 250, 456; water blasting 250-251, 251, 470-471; water cutting 226, 249, 250, 480
High stress seals 174-177, 202, 300, 451, 466
High stress sites 172, 354, 440, 445
Highway, *see* Road

History of chipsealing 3-21
Hoar frost, *see* Frost, ice & snow
Homogeneous section 350-351, *see also* Design variables
Hot chip treatment 178, 180, 471-472
Hot mix asphalt (HMA), *see* Asphaltic concrete
HSE (Health & Safety in Employment) Act 26
HSNO (Hazardous Substances & New Organisms) Act & Regulations 26
Hysteresis 123; *see also* Skid resistance

I

Ice, *see* Frost, ice & snow
Ignition Point of bitumen, kerosene 26
Incompatibility in PMBs 293
In-service performance, *see* Performance of chipseal
Inspection 121, 138, 140, 182, 199, 233, 380, 399, 479
Instability, *see* Layer instability
Instrumentation for binder application rate 396-397; for bitumen distributor 394-396; for spray control 398; for temperature measurement 395-396; *see also* Equipment for chipsealing
Inventory of assets 138, 144-145; dTIMS 145; RAMM 145-146; PMS 137-144
Investigatory Levels 121; & crashes 121; & skid resistance 121; & T/10 181-182; *see also* Skid resistance

K

Kerb & channel (K&C) preparation 234
Kerosene 12, 26, 46, 51-52, 94-95, 203, 248, 272, 276, 280, 283, 301, 302, 429-431, 449, 472-474, 473; in design 355, 358, 360, 362-364
Land Transport Safety Authority 20
Land Transport New Zealand 20
Layer instability 111, 113-116, 115, 177-179, 180; binder:stone ratio 177-179, 180; cumulative seal depth 177; options for 178-179, 180; recycling 179, 478-479, 478; sandwich seal for 60; shallow shear failure 114-115, 115; voidfills for 59
Legislative requirements 26
Level of service 137, 138, 139-140, 144, 145, 154, 180
LGA (Local Government Act) 146
Lichen & preseal preparation 254
Life cycle of chipseal 150-155, 154; ageing & oxidation 93, 100-102, 237, 270, 466, 480; chip loss & weather 111; cracking & hardness 100-102, 111; economic design 150-155, 151, 153; end of life cycle 100-102, 108-109, 155, 154; flushing & layer instability 111-117; impacts on seal design 150-156; long-term performance 100-102, 118-119;

polishing 110, 126; post-construction performance 93-100; short life 110-117; soft substrate 112-113; texture & traffic 101, 103-105; worked example 153; *see also* Asset management, Chipseal selection, Performance of chipseal

Loading on chipseals 44-45, 46, 100-102, 152, 153, 182, 189, 266-270, 469

Localised failures 470-476

Long-term performance 100-102; effect of traffic 6, 98-99

Longitudinal cracking 79, 81; RAMM definition 81; *see also* Cracking

Loss of diluent 94-96, 95

M

Macadam 3-4

Macrotexture 46, 85, 85, 122-124, 122, 123, 124, 156, 440, 464; chipseal selection for 173, 200, 202, 249, 332, 477; ESC 129; PSV 130-131; frost 198, 200-202; OGPA 477

Maintenance strategies 147-150

Major failures 476-479

Management systems, *see* Asset management

Management for cold conditions, *see* Frost, ice & snow

Marsden Point refinery 9, 98, 262, 359

Materials for chipsealing 261-322, 424-425; *see also* Additives, Adhesion agents, Antifoaming agents, Binder, Bitumen, Chip, Cutter, Emulsion, Flux, PMB, PME, Polymers, Precoating, Slurry

Materials for slurry seals 320-322

Mean profile depth (MPD) 86-87, 87, 198-199, 199, 200, 200, 358

Mean Summer SCRIM Coefficient, *see* MSSC

Membrane seal 72

Microclimate 358

Macrotexture 46, 86-87, 122, 122, 124, 129, 250, 301, 313, 480; masked by binder 86-87, 156, 301, 466; repair of 250, 480; *see also* Skid resistance

Middle East oil 8, 9

Milling (scarifying) 190, 244, 478-479

Ministry of Works (MOW) 20

Ministry of Works & Development (MWD) 20

Model (modelling) 19, 140, 145-147, 146, 178, 199, 208, 211-212, 357, 358

Modulus of bitumen 266-270

MSSC 126-129, 127, 128, 129; *see also* Skid resistance

Multicoat seal (multiple coats) 46, 55, 108, 172, 178-179, 191; design 341, 347-350, 353, 367; layer instability 113-116, 477, 478; *see also* Dry lock, Racked-in, Two coat, Sandwich, Wet lock seals

N

National Roads Board (NRB) 5, 20

National Environmental Standards (NES 2004) 34, 250

New Zealand, chipsealing in 3-21; length of road 7; map vi

Noise, definition 204; *see also* Traffic noise

NOMAD 147

Norsemeter RoAR 120, 182

Nozzles for spraybar 380-382, 381, 382-386; adjusting 383, 385-386, 386; conical, slotted, V-jet 381, 381; & viscosity 382

O

OGPA, OGEM, *see* Open graded mixes

Oil, shortage in 1970s 13; sources 7-10; uses 48, 262, 272; heating system 17; *see also* Bitumen sources

Open graded mixes as repair 187, 248, 252, 477; OGPA 72, 176, 187, 202, 248, 252-253, 253, 299, 342, 477; OGEM 72, 252, 253, 342, 463

Operational hazards 28-29, *see also* Hazards

Operational plant, *see* Equipment for chipsealing

Outputs of asset management 138, 142-143; current works programme 138, 143; forward works programme 138, 142-143, 146-147, 149; *see also* Asset management

Overlay 179, 433, 470; *see also* Granular overlay

Oxidation, 93, 100-101, 237, 270, 466, 480; *see also* Ageing, Hardening

P

Particle size (psd, PAP, AP) 67, 307, 318, 320

Patching, timing of 226

Pavement, construction & rolling 227; definition 41; flexible 44; functions of 44-46; layers 41, 42-43, 44-46; rigid 44; stresses in 44-46; surfacings 44, 49-76; terminology 41-46; *see also* Basecourse, Chipseal surfacings, Defects, Pavement repairs, Soft substrate, Sub-base, Subgrade

Pavement defects, *see* Defects

Pavement failure, *see* Failure

Pavement hardness 354; *see also* Soft substrate

Pavement layers, *see* Basecourse, Chipseal surfacings, Soft substrate, Sub-base, Subgrade

Pavement lives 151-155; worked example 153; *see also* Performance of chipseal

Pavement Management System (PMS), *see* Asset management

Pavement preparation, *see* Preseal preparation

- Pavement repairs** 233-253; chip loss 245-246; cracking 174, 236-240; deformations 241-244; depressions 241-242; digouts 236; flushing 247-251; permeable surfaces 252-253; potholes 242-244; prevention of chip loss 480-481; reseals 236-253; rough surfaces 244; shear failures 242-244; surface texture 245-253; weak areas 242-244; wheel ruts 241-242; *see also* Remedial treatments
- Pavement types** 44; *see also* Asphaltic concrete, Chipseal surfacings, Slurry seal, Specialist surfacings
- Penetration grade & testing** 262-263
- Penetrometer** 243
- Performance of chipseal** 6, 93-119; & ageing, cracking 93, 101; expected life 93, 108-107; in-service performance 93; long life 100-102, 118; loss of diluent 94-96; post-construction 93-100; & rolling 96-97; short life 110-117; & skid resistance 119-131; & temperature 97-100; & texture 101; & traffic 100-102, 101, 103-105, 104, 105; & voids 335-336, 336; *see also* Life cycle of chipseal
- Permeable & absorptive surfaces** 252-253
- Personal Protective Equipment**, *see* PPE
- Plant for chipseal construction**, *see* Equipment for chipsealing
- Plastomers**, *see* Polymers
- PMBs (PMB seals)** 291-305; additives for 301, 302; as emulsions (PMEs) 285, 302; failure 304; handling 293, 453-454; hazards 294, 453; history 5, 11, 291; manufacture 292-293; specifications for 292, 303-304; storage 293; testing 292; uses 291, 297-301; *see also* PMB construction, PME, Polymers
- PMB application rates** 301-302
- PMB construction** 451-454; material selection 451-452; spray rate calculations 452-453; spray temperatures 453
- PMB uses** 297-301; bandaging 298; crack sealing 298-299; high stress seals 300; SAMs 298-299 SAMs 299; severe climates 300-301
- PMEs** 285, 302; construction 454; materials 447; spray rate calculations 447; *see also* Polymers
- PMS (Pavement Management System)**, *see* Asset management
- Pneumatic-tyred roller (PTR)** 407-408, 407
- Polished Stone Value**, *see* PSV of chip
- Pollution control** 34, 168, 420, 451
- Polymers** 11, 291-305; & binder design 361; crumb rubber 297; elastomers 294-296; plastomers 296-297; *see also* PMBs
- Porosity** 186, 204, *see also* Open graded mixes
- Porous surfacings**, *see* OGPA, OGEM
- Portland cement use** 44, 322; & stabilisation 231-232
- Post-construction performance** 93, 94-100; loss of diluent 94-96; & rolling 96-97; settling down 93; & temperature 97-100; & traffic 6, 100-105, 107, 104, 105
- Potholes** 83-84; RAMM definition 84; repairs 84, 242-244; *see also* Defects
- PPE (Personal Protective Equipment)** 28, 29, 401
- Practical aspects of design**, *see* Design variables
- Precoating** 11-12, 176, 275-278, 424-425, 471-472; design 349-350, 361, 364; handling 277; hazards 277-278, 424; manufacture 276-277
- Preparation**, *see* Preseal preparation
- Preparation for bridge surfacing**, *see* Preseal preparation
- Preparation for construction before sealing day** 419; contract requirements 420; for emulsion seal 446-451; on the day 438-445; site assessment 420-422; techniques 426
- Preseal preparation** 223-254; for bridge surfacings 194; drainage & shoulder repairs 233-236; existing pavements (reseals) 224-225; first coat seals (new, unsealed) 50, 223, 225-228; goals 223; investigation 233-234; pretreatment seals 168, 225; priming 168, 356; removal of deleterious matter 253-254; surface texture repairs 233, 245-253; timing 225-226; *see also* First coat seals, Prime coats
- Pretreatment** 50, 53, 168, 225, 252-254, 253, 351; *see also* Preseal preparation
- Prime coat, Prime, Priming** 12, 51-52, 165, 168, 169, 194, 240, 275, 304, 356
- Principles of asset management**, *see* Asset management
- Principles of chipsealing**, *see* Design algorithm
- Principles of seal selection**, *see* Chipseal selection
- Prioritisation**, *see* Asset management
- Product development** 143
- Production of aggregate**, *see* Chip production
- Production property tests**, *see* Chip properties & tests
- Programming reseals** 143, 145-148, 156, 170; *see also* Chipseal selection, Current work programme, Forward works programme
- PSV (Polished Stone Value)** 13, 48, 129-131, 130, 182, 313-315, 314, 367; equation 130, 184-185; polishing of chip 110, 120, 131, 182; & seal selection 182-186, 202; test 313-315, 314; worked example 185-186; *see also* Skid resistance
- Public Works Department (PWD)** 20
- Pumps & pumping systems** 390-393, 391, 397, 397; for distributors 390-393; types A, B, C 390-393; *see also* Circulating systems, Equipment for chipsealing, Instrumentation

Pumping (defect) 78, 87, 237, 239
P/17 specification 135-136, 148-149

Q

Quality control of aggregate 311; *see also* Calibration
Quarry aggregate 308

R

Racked-in seal 56-58, 56, 74, 108, 164, 176, 216-217, 300, 304; construction 426-427, 437, 440; design 348, 354, 368; use in snow 57, 202

RAMM 19, 77-85, 224; & exception reports 145, 180-181; & forward works programme 145, 146; inventory & condition data 145-146; & road information 144; treatment selection algorithm 145; *see also* Alligator cracking, Block cracking, Edge break, Flushing, Longitudinal cracking, Potholes, Rutting, Scabbing, Transverse cracking

Rain effects, *see* Weather

Rates, application, *see* Application rates, Binder, Chip, Bituminous emulsions, PMBs, PMEs

Ravelling 82; *see also* Defects

RCA, *see* Road Controlling Authority

RD286, *see* Design algorithm

Reconstruction 142, 146, 179; alternatives to 74-76, 174, 298-299

Recycling seal 172, 179, 180, 478-479; *see also* Environment & construction

Rehabilitation 142, 146, 155, 163, 166, 179, 224, 225, 237, 481

Rejuvenating seal 73-74, 164, 169

Remedial treatments 469-479; for layer instability 178-179; restoring skid resistance 479-480

Remedial treatments for localised failures 470-476; chip removal 476; diluent & chip 472-474, 473; gritting 229, 471; hot chip 178, 471-472; sandwich sealing 60, 179, 248, 369, 474-475, 475; water blasting 178, 249-251, 251, 470-471, 480; wet lock 343, 475-476; *see also* Pavement repairs

Remedial treatments for major failures 476-479; dig out & replace 478; fabric use 74-75, 240, 349, 369, 476-477; granular overlay 179, 238, 477, 479; open-graded mixes 187, 248, 252, 477; recycle 244, 478-479, 478; *see also* Pavement repairs

Remedial treatments at short notice 479-481

Re-orientation of chip 331, 333, 362; *see also* Embedment, Compaction

Repairs, *see* Pavement repairs, Remedial treatments

Reseals 52-53, 108-111, 152, 163, 164, 166, 169-170, 202, 209, 224-225; & AWPT 154-155; design 331, 343-344, 354-357, 365; for defects 106-107; for

end of life 154-155; reasons for 106-108, 106, 469; & second coat seals 356-359; selection 172, 173-174, 180, 180-181, 447, 474, 478, 479-480; & temperature 357-359, 428; timing 156, 226; & traffic volume 103-105, 104, 105, 107; worked example 155, 370-374; *see also* Chipseal selection, Design algorithm

Reseal preparation, *see* Preseal preparation, Chipseal selection

Reseals as repairs 479-480; for chip loss prevention 480; as crack repair 236-270; at short notice 479-481; unscheduled 479-480; *see also* Preseal preparation, Remedial treatment

Research 5-6, 10, 93-118

Residual binder design, *see* Binder (residual) in chipseal design

Resurfacing, *see* Surfacing, Chipseal surfacings

Retention of chip, *see* Chip loss

Rheological properties 262-271

Rigid pavement 44

Ring & Ball test (ASTM D36) 271, 342

Risk assessment, *see* Asset management

Risks with precoating 277-278; environmental 278; safety 277; tracking 278

RMA (Resource Management Act) 26

Road 41; surfacings for 41, 49-76; terminology 41-46

Road asset management, *see* Asset management

Road Controlling Authority 7, 19, 20, 34, 41, 120, 144, 145, 151, 187, 197, 208, 212, 214, 214, 215, 343, 421, 455, 479, 480

Road factors affecting skid resistance, *see* Skid resistance

Roadmarking 187-188

Road traffic noise, *see* Traffic noise

Road user safety & seal selection 181-187; & crashes 181-183; PSV 184-186; road marking 187-188; skid resistance 181-186; treatments for 182-185; worked example 185-186; water spray 186-187

Road Weather Information System (RWIS) 199; *see also* Frost, ice & snow

Roading New Zealand (RNZ) 25, 31, 32, 387

Roadway 41

RoAR Norsemeter 120, 182

Rollers & rolling 1-2, 18, 96, 407-409, 425, 438-440; combination 409, 409; pneumatic-tyred (PTR) 407-408, 407; roller spreader 18; rubber coated vibrating steel drum 408, 408; rubber-tyred 18

Rolling 96-97, 425, 438-440; compaction effect 96-97, 96, 97; drum rollers 408, 440; research 5, 6, 48, 96-97, 112, 113, 331, 363, 440; by traffic 97, 363

Rolling resistance 13
Rollover of chip, *see* Embedment of chip
Rotary broom 224, 410, 411
RTFO (Rolling Thin Film Oven) test 265
Rough surfaces, Roughness 86; *see also* Defects, Pavement repairs
Rubber use of 11, 291, 295, 296; crumb 11, 297
Rutting 77, 77-78; RAMM definition 78; *see also* Defects
RWIS 199, *see also* Frost, ice & snow

S

Safaniya bitumen, *see* Binder
Safety, *see* Hazards, Skid resistance
SAM seal 65-66, 164; design 66; cracking 65, 174, 238, 240; flushing 248; PMB 295, 298-300
SAMI seal 72, 172, 174, 240, 295, 299-300
Sampling bitumen emulsions 287-288; chips 311, 314
Sand circle test T/3 172, 332-333; sand circle T/3 equation 333; & texture 332-333, 333; & ALD/16 rule 352-354
Sandwich seal 59, 60-61, 60, 61, 164, 172, 179, 180, 248, 333; design 348-349, 369; & layer instability 61; layer sequence 60, 475; as repair 179, 248, 369, 470, 474-475, 475
Scabbing 82, 102, 106, 467; RAMM definition 82; *see also* Chip loss
Scalds 30
Scarifying (milling) 190, 478-479
Screening, *see* Chip production
Screen (strainer), *see* Bitumen distributor
SCRIM, *see* Skid resistance
Scuffing, tyre scrub 175, 202, 466; *see also* High stress seals
Seal, *see* Chipseal, Chipseal selection, Chipseal surfacings, Chipsealing
Seal design, *see* Design algorithm
Seal performance, *see* Life cycle of chipseal
Sealing chips, *see* Chip
Seasonal variation, *see* Skid resistance
Second coat seal 52-53, 168, 169, 367; design 356-359
Segmentation, *see* Design variables
Sensitivity of design algorithm 344-345, 353; to changes in variables 346-347
Settling down period, *see* Post-construction
Settlement 287, 289, 446; *see also* Bitumen emulsion
Shade effects, *see* Weather
Shear failure 78-80, 87, 111, 113-116; repairs 242-244, 478; *see also* Defects
Short life, *see* Life cycle of chipseal
Shoulder 42
Shoulder repairs, *see* Preseal preparation
Shoving 77, 78, 79, 87; RAMM definition 78; *see also* Defects
Shrinkage cracking 79, 81; *see also* Cracking
Sideway Force Coefficient (SFC), *see* Skid resistance
Single coat seal 11, 53, 53-54, 74, 97, 103-104, 103, 104, 152, 163, 164, 172, 176, 177, 202, 217, 298, 367; design 331, 334, 337, 347; worked example 153, 370-374
Site assessment, *see* Chipseal selection
Site-specific adjustments, *see* Design variables
Skid resistance 119-131, 181-189; BPT test 120, 182, 315, 315; & chip properties 129-131; control sites for 126-127, 129; correction factor 129, 129, 185-186; & crashes 119-122, 181, 183, 201; equilibrium skid resistance 125; ESC (year on year variation) 127-129, 128, 129; GripTester 120, 120, 182-183; hysteresis 123; investigatory levels 121; measuring 119-120, 120, 182-183; MSSC (within year variation) 126-129, 127, 129, 183; Norsemeter RoAR 120, 120, 182-183; polishing 110, 125, 126, 128, 129; PSV 48, 110, 129-131, 130, 182, 184-186, 313-315, 314, 367; SCRIM 119-120, 120, 182, 183; seasonal variation 125-129, 125, 127, 128, 129; Sideway Friction Coefficient (SFC) 130, 182; & traffic speed 123-124, 124; traffic volume & type 130, 130; tyre interface 122-124, 123, 124; water film (aquaplaning) 123-124, 123, 241; *see also* Frost, ice & snow, Macrotexture, Microtexture, Texture
Skidding, *see* Crashes, Skid resistance
Slick surface 86; *see also* Flushing
Slurry seal 66-71; aggregate types for 67, 320-321; cape seal 69-71; cement for 321-322; durability 69; emulsion 68, 321; air temperatures 68; materials 320-322; & road noise 67-68; water 322
Snow, *see* Frost, ice & snow
Soft substrate (soft soils) 3, 74-75, 111-113, 462; effects on algorithm 341-342, on granular bases 112; over HMA 112, 113; over pavement repairs 112, 114; over weak pavements 113
Softening point of bitumen 271, 303
Solubility of bitumen 264
Solvent, use 472-473, 473; *see also* Cutter, Flux
Sound definition 204, *see also* Traffic noise
Source property tests, *see* Chip properties & tests
Span, *see* Bridges
Specialist surfacings 73-76; calcined bauxite 73; enrichment seal 73; fog coat 73; geotextile seal 74-76, 74, 75; rejuvenating seal 73

Specifications 9-10, 13; B/2 225-228, 356; C1 42, 43; M/1 262-266, 271, 285, 288, 360; M/4 225, 228, 231; M/6 48-49, 307, 312-313, 316-318, 320, 364, 367, 432; M/10 307; P/11 211, 477; P/17 100, 135, 148-149, 337, 342, 420; P/26 250; T/3 86, 333, 339, 372; T/10 121, 181, 184, 187, 315, 367, 480; for PMBs 292, 303-304

Spillage hazard 214, 419-420

Sprayer, *see* Bitumen distributor

Sprayer calibration 17-18, 389-390, 389; adjusting 383-386; adjusting gauge 385-386; BCA E/2 compliance 380, 382, 390; spray application chart 380, 390

Spraying 380-389, 394-398; calculations and tables 428-431, 433-434, 447-448, 452; for construction 441; coverage (overlap) 15, 380-386, 383-386; difficult areas 443-445; hand spraying 9, 14, 19, 388, 389, 415-416, 444-445, 444; history 14-15; practical aspects & design 350; spray runs 442-443; spray temperature 16, 27, for bitumen binder 432, 433, 434, for emulsions 448-449, for PMBs 453; start-finish 388, 389, 442

Spraying equipment, *see* Spray nozzles, Spraybar

Spray nozzles 380-386; end nozzles 384, 441; types 15, 380-383, 381, 383, 384-386, 441

Spraybar 380-389; control 386, 398; height 441; operation 384-389; variable rate 382-383, 441, 443

Spraying hazards, *see* Hazards

Spreader, *see* Chip spreader

Stabilised pavements, Stabilisation 231-232, 238, 279, 478; preparation for reseal 112, 231-232, 244; failure of 81, 231-232

State highways NZ, length 7

Strategy, *see* Asset management

Steep grades, effect on algorithm 342-343, 351, 362, 373-374; high stress seals for 174, 177

Stiffness modulus of bitumen 266-271, 268-271

Stockpiling 277, 311, 371, 419, 455; *see also* Chip production

Stone, *see* Aggregate, Chip

Stone mosaic 227, 231, 319, 369, 407, 451

Storage of bitumen emulsion 286-287; of PMBs 293

Strainer (screen) maintenance 396

Strategy, *see* Asset management

Stress factor in skid resistance 185; worked example 185-186

Stresses in pavements 44-46, 45, 78

Stressed sites 110, 130, 151-153, 174-177, 229, 245, 295, 300, 354, 422, 445, 466; & design 341, 354; & seal selection 53-55, 57, 61-71, 72, 76, 167, 174-177, 182, 184-186, 201-202, 216, 295, 297, 300, 426, 446, 451, 474, 477

Stripping, *see* Chip loss

Sub-base 44

Subgrade 41

Substrate, *see* Soft substrate

Suction sweeper 411; *see also* Brooms

Surface texture repairs, *see* Preseal preparation

Surfacing selection, *see* Chipseal selection

Surfacings 49-76; *see also* Asphaltic concrete, Chipseal surfacings, Slurry seal, Specialist surfacings

Sweeping & sweepers 224, 229-230, 254, 409-412, 411; *see also* Brooms

Synthetic aggregates 306

T

T/3 sand circle equation 333

Tachometer 394-395

Tanker, Tankwagon, *see* Bitumen distributor

Tar, coal 3-4, 7

Tar kettle 8, 8

Tar macadam, Tarmac 3-4

Temperature (for chipsealing) of binder 432-434, 448; measurement of 395-396; & cracking 100, 111; & cutter 95; & properties 98-99, 111, 113, 266; trials 97, 98-99, 99

Temperature (weather) effects if low 48, 98, 301, 359, 439, 445; if high 99, 301, 357-359; on performance 97-100, 301, 357-359, 445; on roads 360, 362-363; of seasons 98, 111; of shading 445, 451; *see also* Frost, ice & snow, Weather

Terminology 41-46

Texture 46, 85-87, 85, 87, 122-124, 122-124, 200, 200, 216, 333, 355, 357, 359; defects & repair 58, 60, 168, 173, 225, 243, 245-252, 246-251, 461-478, 463-465, 467-468, 473, 475, 478; theory 96, 96, 97, 97, 100, 101, 103-107, 112-113, 113, 148, 166, 181-182, 186-187, 198-200, 202, 204, 211, 304, 312, 332, 334-335, 339, 349, 355, 357-359, 420, 426, 455; variation 352-354, 372-373; *see also* Design algorithm, Macrottexture, Microtexture, MPD, Sand circle test

Texture loss 86, 87, 461-466; & binder rise 463-464, 463; bleeding 464, 465-466; & chip embedment 462-463; chip loss 466-468, 467, 468; & chip re-orientation 462; flushing 464, 465; & high binder application 462; tracking 464-466, 465

Texturising seal 166, 168, 172, 225, 244, 252-353

Thermostat control 16, 400; *see also* Instrumentation

Thin ice, *see* Frost, ice & snow

Timing, *see* Chipseal selection, Preseal preparation

Timeline 4-5

- Tracking** 56, 86, 97, 114, 156, 215-216, 217, 278, 301, 343, 358, 358, 424, 444, 464-466, 465, 469; prevention of 57, 65, 68, 217, 300, 303
- Traffic factor**, *see* Design algorithm
- Traffic & long-term performance**, *see* Performance of chipseal, Life cycle of Chipseal
- Traffic management (COPTTM)** 25, 28, 33, 387, 401, 423, 438-439; for compaction 176, 439; for construction 419, 423, 425; *see also* COPTTM
- Traffic noise 204-212**; & community 204-209, 209, 213-214, 215, 421; measure of 205, 210-211; reduction of 211-212; sources of 204-208, 206, 207, 244; & seal selection 13, 63, 67-68, 70, 211-212, 217, 370
- Traffic & skid resistance**, *see* Skid resistance, Traffic noise, Vehicle speed
- Traffic stress**, *see* Stressed sites, Modulus of bitumen
- Training** 20-21, 25, 30
- Transfund NZ** 20, 146
- Transit NZ** 7, 19-20, 106-108, 110, 121, 128, 212, 292, 480; COPTTM 25, 28, 33, 387, 401, 423, 438; *see also* Specifications
- Transverse cracking** 79, 81; RAMM definition 81; *see also* Cracking
- Treatments**, *see* Chipseal selection, Pavement repairs, Preseal preparation, Remedial treatments,
- Treatment length** 139, 140-142, 148, 152, 178, 181
- Treatment selection algorithm (in RAMM)** 145
- Treatment selection**, *see* Chipseal selection
- Turpentine** 26, 52, 95, 248, 261, 272, 472; *see also* Cutter
- Two coat seal** 49, 54-56, 54, 62, 69, 105, 108, 164, 192, 425, 426, 440, 484; design of 334, 347-348, 353, 368, 369; compatibility of layers 368-369, 368, 426; & chip application rate design 369; materials 292, 298-300, 302, 304, 447, 454; seal selection 57, 58, 63-66, 74, 142, 153, 164, 167, 176, 202, 211, 212, 216-217, 238, 253
- Two coat as first coat seal** 54, 55, 167, 471
- U**
- Upcreaming** 287, 289, 446; *see also* Bitumen emulsion
- Urban variable in design algorithm** 341, 343-344, 347, 351, 370-374; surfacings for 61, 67, 68, 70, 164, 179, 187, 208, 210, 213, 216, 238, 244, 341, 411
- V**
- Vacuum broom** 411-412, 411; *see also* Brooms
- Vapour**, *see* Hazards
- Vapour venting** 111, 117, 117, 247, 463
- Variables for design**, *see* Design variables
- Vegetation control** 42-43, 199, 420; *see also* Weather
- Vehicle speed** 28, 48, 59, 123-124, 124, 169, 204-205, 210-211, 351, 390-391, 394, 396, 402, 404, 451, 464; *see also* Skid resistance
- Vehicles for chip spreading**, *see* Chip spreader, Equipment for Chipsealing
- Verge**, *see* Shoulder
- Vibrating roller**, *see* Rollers
- Viscoelasticity** 94, 116, 267-270, 474
- Viscometer** 263, 263, 288, 289
- Viscosity**, of bitumen 46, 48, 97, 262-264, 266, 271, 275, 363, 439, 440, 445; of bitumen emulsions 11, 280, 284, 284, 288, 288, 290, 302, 447, 448; of cutback binder 51, 52, 94, 116, 179, 272, 361, 362; effect of adhesion agents 274, 274, 275, 275, 276, 361; of PMBs 293, 295, 300, 301-302, 452-454; spraying 10, 46, 382, 397, 398; test 263, 263, 264, 288; viscometer 263, 263, 288, 289; viscosity-temperature relationships 86, 97-99, 98-99, 358, 358, 362, 363, 363, 445
- Voids basic concept** 5, 6, 98, 98, 99, 99, 103-105, 103-105, 173, 331, 332, 334-335, 334, 336, 337, 337, 343, 361, 453; chip embedment 103, 298, 299, 301, 334-335; clogged 165, 248, 312, 318, 471, 477; design algorithm 252, 337, 338, 346, 365, 366; Hanson 1935 input 5-6, 6, 331-332; OGPA 72, 211, 253, 477; & single coat seals 103-104, 103, 104; & texture 332-333; & traffic 6, 6, 103-105, 332-334; & two coat seals 105, 105; volume of HCV 103-105, 338-339
- Voidfill seal** 58-59, 67, 74, 109, 163, 164, 166, 173, 252; binder:stone ratio 59, 116; design of 59, 352, 360, 367, 447; materials for 67, 286, 360, 447; seal selection 74, 163, 163, 167, 173, 331, 348, 356, 481; texture depth allowed 59, 348, 352; as repair 481
- Volcano** 117, 117; *see also* Vapour venting
- W**
- Water blasting** 168, 178, 180, 249-251, 251, 470-471, 480
- Water contamination**, *see* Hazards, Contamination of run-off
- Water cutting** 226, 249-250, 250, 480
- Water film & skid resistance (aquaplaning)** 123-124, 123, 124, 131; & binder-chip adhesion 361; *see also* Skid resistance
- Water spray & seal selection** 186-187
- Weak substrate**, *see* Soft Substrate

Weather 445; & construction 168-169, 182, 203, 230, 240, 304, 346, 360, 364, 428, 438, 439, **445**, 474; effect of high temperature 65, 84, 86, 112, 156, 301, 302, **357-359**, 427, 462, 464-465; effect of low temperature 111, 173, 195-201, 346, **359**, 439, 466; effect of rain 111, 126-128, 150, 182, 186, 230, 232, 274, 466, 467; effect of shade 196, 198-199, 245, **362-363**, 363, 445, 469; & emulsion 302, 360, 364, 446, 450; & PMBs 65, 304, 451, 454; rain & pollution 168, 278, 424; *see also* Frost, ice & snow, Temperature (weather)

Weathering resistance test for chips 312-313;
see also Chip properties & tests

Weed spraying 226, 254

Wet lock 62-63, 62, 164; as repair 343, 470, 475-476; binder:stone ratio 62; design of 348; materials for 447; seal selection 164, 202

Wet road, crashes & skid resistance 122-124, *123*, *124*;
see also Skid resistance

Wheel ruts 77-78, 233, 241-242, *243*, 408, 440

Wooden bridge decks 52, 191, *192*, 194

Worked examples, application rates 370-374;
for chip volume 435; conversion of pph 429-431;
economic seal selection 153, 155; for PSV 184;
single coat seal 370-374; for skid resistance
treatment 185, 186

Y

Yearly variation, *see* Skid resistance; within year,
see MSSC; year on year, *see* ESC

Z

Zone, no-smoking 27; climatic 98; weak substrate 243;
tyre print 123

